

# FTX250



**Tracked Carriers**  
**Swamp Track Low**  
**Ground Pressure**



# Technical Specifications

GENERAL	
Bull Hog Mulcher STD	FTX250 - SLGP
Overall Height	BH120H-2-SD
Overall Height	114"
Length of Tractor Only	290"
Length of tractor with Bullhog®	324"
Weight Tractor Only	24,480 lbs
Weight of Tractor with Bullhog®	29,880 lbs
Width of Tractor Only	99"
Width with Bullhog®	101"
Engine	
Air Cleaner	Dual w/ Pre-Cleaner
Cooling	Water Cooled
Fuel Tank Capacity	88 US gal
Horsepower	250 hp
Engine Make / Model	Cummins C8.3L
Maximum Rated Torque @ RPM	830 ft lbs @ 1300 rpm
Number of Cylinders	6
Hydraulic	
Hi-Flow Circuit PSI/GPM	6000 psi / 75gpm
Low Flow Circuit PSI/GPM	2000psi / 20 gpm
Hydraulic Reservoir	71 gallons
Undercarriage	
Ground Pressure per SAE J1309	3.9
Ground Pressure per SAE J1309 at 6" depth	3.3
Track Gauge	66"
Track Width	33"
Undercarriage Design	Steel & Rubber
Travel Speed (low / hi)	1 / 5.3 mph
Ground Clearance	15.5"

Purpose built for professional mulching. Well suited for all around use or specifically where ground conditions, ground disturbance, or crossing pavement is an important consideration. Choose the SLGP (Super Low Ground Pressure) track for ultra low ground pressure applications good travel speed and the ability to track across roads.

## FEATURES

- Rear Mounted 20,000 Lb Winch w/remote
- Rear View Color camera
- On-board compressed air
- Lift Over 11' high
- 12-Volt power Outlet In Cab
- Excellent engine compartment access
- Front and rear flood lighting
- Dual engine pre-cleaners
- Heat/AC
- ROPS, FOPS, Lexan Windows
- Low Ground Pressure

## APPLICATIONS

- Land Clearing, R.O.W. and Vegetation Management
- Rubber track Models allow for easy travel without damaging roadways or surfaces
- Cut brush and trees quickly down to a fine mulch
- Low Ground Pressure



## Mulch Where You Couldn't Mulch Before...

- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Safety Is The Responsibility Of The Operator.
- Always insure that your carrier manufacturers safety features, including Falling Object Protection, meet your job safety requirements.
- Specifications subject to change without notice.

1/10

GSA GS-30F-0019S



www.Fecon.com  
E-Mail: sales@fecon.com

Fax: 513.696.4431  
Toll Free: 800.528.3113