

FTX440



Tracked Carrier
Maximizing Productivity
and Uptime In The Woods



Technical Specifications

GENERAL	FTX440 Standard	FTX440 Wide
Bull Hog Mulcher STD	BH350	
Overall Height	129"	
Length of Tractor Only	205"	
Length of tractor with Bullhog®	278"	
Weight Tractor Only	45,960	48,446 lbs
Weight of Tractor with Bullhog®	54,100	57,500 lbs
Width of Tractor Only	102"	125"
Width with Bullhog®	111"	138"
Engine		
Air Cleaner	Dual w/ Pre-Cleaner	
Cooling	Water Cooled	
Fuel Tank Capacity	175 us gal.	
Horsepower	440 hp	
Engine Make / Model	Caterpillar C-13 Tier III	
Maximum Rated Torque @ RPM	1480 ft lbs @1400 rpm	
Number of Cylinders	6	
Hydraulic		
Hydraulic Reservoir	65 gal	
Undercarriage		
Ground Pressure per SAE J1309	6.9	4.9
Ground Pressure per SAE J1309 at 6" penetration	6.1	4.3
Track Gauge	78"	90"
Track Width	24" / 600 mm	36" / 900 mm
Undercarriage Design	Steel	
Travel Speed (low / hi)	2.6 / 3.8 mph.	
Ground Clearance	21"	

The FTX440 mulching tractor leads the field in productivity, serviceability and brute strength for the toughest applications. Equipped with the PTO driven Fecon BH350 Bull Hog, this mulching combination is designed for hard work, reliability and profitably. The FTX440 features a spacious operators cab, large LEXAN® windows for high visibility, and a controls utilizing the interactive Parker IQAN® system. Optimal machine performance, quick operator feedback and excellent service access allows this machine to deliver what you expect from the industry leader.

Accessories

- Available track pads: 24" double, 28" double, 32" triple, 36" triple
- Rear camera with color monitor
- Engine positive air shutoff
- Hydraulic winch 30,000 lbs capacity
- GPS

FEATURES

- Heavy Duty Caterpillar® D6 Class undercarriage
- Air suspended heated seat, climate control, AM/FM/CD radio
- Custom, interactive Parker IQAN® control system for optimal machine performance, quick operator feedback, and ease of troubleshooting
- BH350 Mulcher with hydraulic push bar and trap door; adjustable skid shoes
- Arctic Cold Weather Package including engine coolant heater, Hydraulic tank heater, and snow canopy
- Engine rpm is reduced through an industrial gear box to achieve optimal rotor torque at the mulcher under maximum loads.
- Patented synchronized interface between the mulcher and crawler allows full range of motion through lift and tilt functions.
- Fast and direct access to maintenance and service points by large doors, a sliding cab and a swing-out hydraulic cooler.
- Comfortable cab, user-friendly controls & exterior cab lighting.

- Operators cab must be protected with both properly maintained LEXAN® Glass (or equal) and Falling Object Protection.
- Safety Is The Responsibility Of The Operator.
- Specifications subject to change without notice.

1/10

GSA GS-30F-0019S



www.Fecon.com
E-Mail: sales@fecon.com

Fax: 513.696.4431
Toll Free: 800.528.3113